IN THE CLAIMS

Please amend the claims as follows:

Claims 1-26 (Canceled).

Claim 27 (Currently Amended): A radio communication method by a radio communication system in which output signals are generated from a plurality of information signals and then transmitted respectively at a plurality of different frequencies to a system of a communication partner from N antennas, N being an integer of 2 or larger, the method comprising:

receiving control information by a control signal which is transmitted by the system of the communication partner; and

transmitting transmission signals respectively at the plurality of frequencies from the N antennas based on the received control information, the transmission signals each being generated based on a first operation result, which is obtained by multiplying a first information signal by a first N-dimensional weight vector, and a second operation result, which is obtained by multiplying a second information signal by a second N-dimensional weight vector, wherein

the control information includes weight-related information including a set of the first N-dimensional weight vector and the second N-dimensional weight vector,

the first information signal and the second information signal include one of a set of signals modulated by different modulation schemes and a set of signals encoded by different encoding methods, and

the weight-related information is common to <u>all of</u> the plurality of frequencies <u>used</u> for signal transmission from the radio communication system to the system of the <u>communication partner</u>.

2

Claims 28-30 (Canceled).

Claim 31 (Currently Amended): A radio communication system in which output signals are generated from a plurality of information signals and then transmitted respectively at a plurality of different frequencies to a system of a communication partner from N antennas, N being an integer of 2 or larger, comprising:

reception means for receiving control information by a control signal which is transmitted by the system of the communication partner; and

transmission means for transmitting transmission signals respectively at the plurality of frequencies from the N antennas based on the received control information, the transmission signals each being generated based on a first operation result, which is obtained by multiplying a first information signal by a first N-dimensional weight vector, and a second operation result, which is obtained by multiplying a second information signal by a second N-dimensional weight vector, wherein

the control information includes weight-related information including a set of the first N-dimensional weight vector and the second N-dimensional weight vector,

the first information signal and the second information signal include one of a set of signals modulated by different modulation schemes and a set of signals encoded by different encoding methods, and

the weight-related information is common to <u>all of</u> the plurality of frequencies <u>used</u> for signal transmission from the radio communication system to the system of the communication partner.

Claims 32-34 (Canceled).